

Technical specification sheet

12 S 12 D | Vari Pump

Specifications		
article number		100.152.021
model		12 S 12 D
max. working pressure	bar/Mpa	720 / 72
short description		Vari Pump
capacity oil tank (effective)	cc	12000
number of outputs		1
number of stages		1
first stage output / min.	cc	1200
first stage pressure range	bar/Mpa	0 - 720 / 0 - 72
operator type		electric motor
engine		230 VAC - 1.5 kW - 50 Hz - 1 Ph
speed	rpm	2850
weight, ready for use	kg	46.0
dimensions (LxWxH)	mm	400 x 3200 x 541

Required Accessories		
Control Valve - Single Acting - M 311		100.181.311
Control Valve - Double Acting - M 322		100.181.322

Accessories		
Single-/Double Acting Valve (SADA) M 304		100.172.051
Control Valve - Double Acting - M 323 (Deadmans Function)		100.181.323
Remote Control Valve + Oil Filter - Double Acting - M 326		100.182.321
Pressure Control Valve M 303		100.181.303



holmatro.com

© Holmatro 2024-04-16

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.