
Technical specification sheet

HHJ 20 S 15 Hollow Plunger Cylinder

Specifications			
article number		100.112.030	
short description		Hollow Plunger Cylinder	
model		HHJ 20 S 15	
max. working pressure	bar/Mpa	720 / 72	
tonnage	t	20	
stroke	mm	150	
closed height	mm	389	
capacity	kN/t	223.9 / 22.8	
effective pressure area	Cm ²	31.1	
required oil content (effective)	CC	467	
connection		A 118	
cylinder type		hollow plunger	
acting type		single	
return type		spring	
material		steel	
weight, ready for use	kg	18.0	

Holmatro Martic Jacks, tools and parts	
Notimate Marine CE	



Technical drawing dimensions		
dimension A	mm	389
dimension B	mm	100
dimension C	mm	50
dimension D	mm	90
dimension E	mm	31
dimension F	mm	377
dimension R	mm	27
dimension S	threadsize	M38x1,5
l type		[12]

Standard supplied with

• High flow female coupler A118

Hollow saddle (with the exception of the HHJ5S2.5, HHJ12S5 and HHJ12S15)



holmatro.com

© Holmatro 2024-07-12

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.

