

Technical specification sheet

HJ 100 G 15 SN | Locknut Cylinder

| Specifications | | |
|----------------------------------|-----------------|------------------|
| article number | | 100.082.000 |
| short description | | Locknut Cylinder |
| model | | HJ 100 G 15 SN |
| max. working pressure | bar/Mpa | 720 / 72 |
| tonnage | t | 100 |
| stroke | mm | 150 |
| closed height | mm | 323 |
| capacity | kN/t | 1029.3 / 105 |
| effective pressure area | cm ² | 143 |
| required oil content (effective) | cc | 2150 |
| connection | | A 118 |
| cylinder type | | lock nut |
| acting type | | single |
| return type | | gravity |
| material | | steel |
| weight, ready for use | kg | 71.0 |

| Technical drawing dimensions | | |
|------------------------------|----|------|
| dimension A | mm | 323 |
| dimension B | mm | 190 |
| dimension C | mm | 135 |
| dimension D | mm | 70 |
| dimension E | mm | 25 |
| dimension F | mm | 287 |
| I type | | [I1] |

| Standard supplied with | |
|---------------------------------|--|
| • High flow female coupler A118 | |
| • Flat saddle | |

| Accessories | |
|----------------------------------|-------------|
| Tilting Saddle HJ 100 - 150 (SN) | 100.181.044 |

