
## **Technical specification sheet**

## **ICU 20 STH 30** Stationary Cutter - 2 hand controlled

Specifications		
article number		170.012.080
model		ICU 20 STH 30
max. working pressure	psi	7252
blade type		30 standard
cutter type		stationary - horizontal assembled blades and two hand operation
short description		Stationary Cutter - 2 hand controlled
max. cutting force	lbf	55303
max. cutting opening	in	6.2
required oil content (effective)	oz	2.8
weight, ready for use	lb	58.6
temperature range	°F	-4 +176
max. cutting diameter round bar (S235 acc. to EN 10025-2)	in	0.9
max. cutting diameter round tube (E235 acc. to EN 10305-1), based on wall thickness 2mm/0,08in	in	3.9
catalytic converter	%	95
number of cuts per day		200
number of operating hours per day		24





Technical drawing dimensions		
dimension A	in	25.6
dimension B	in	14.2
dimension C	in	12.3

## Required Accessories

Balancer, 25 - 30 kg	130.581.000
----------------------	-------------

Accessories	
Blades, Set 10 Cable	170.013.047
Blades, Set 40 Straight	170.013.038



## holmatro.com

© Holmatro 2024-07-04

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.

